



An Oshkosh Corporation Company



DOMINATOR[®] III

Mechanics Body

With enhanced strength and stability for higher crane loads, numerous configuration possibilities, and a body rating of 81,000 ft-lb (11.1 tm), the Dominator III mechanics truck offers exceptional performance in virtually any industry. With the Dominator III mechanics truck, you don't have to bring your equipment into the shop for service, because the shop comes to you.

> BASE BODY SPECIFICATIONS

Body Size	11'	11'	14'	14'
Body Configuration	LH AR, RF RSD	ALL RSD	LH AR, RF RSD	ALL RSD
Body Rating	81000 ft-lb	81000 ft-lb	81000 ft-lb	81000 ft-lb
Body Weight ¹	4090 lb	4109 lb	4772 lb	4806 lb
Body Width	96"	96"	96"	96"
Storage Capacity	159.7 ft ³	164.9 ft ³	210.7 ft ³	215.4 ft ³
Angle of Departure	13°	13°	13°	13°
Chassis CA ²	84"	84"	84"	84"
Max. IMT Crane Model	12000 25'	12000 25'	12000 30'	12000 30'

Notes: 1) Includes doors, sidepacks, workbench. 2) Does not include welder deck



> STANDARD FEATURES

- Body rating — 81,000 ft-lb (11.1 tm)
- Enhanced strength and stability for higher crane loads
- Multiplex electrical system with programmable logic
- Workbench
- Rear access package

> OPTIONS

- High-intensity light package
- Drawers and drawer sets
- Standard adjustable shelves
- Divided adjustable shelves
- Stabilizers — manual and hydraulic
- Energy-absorbing boom support
- Workbench vises and vise plates
- LED work lights and compartment lights
- Compartment pressurization system
- Master lock system
- Air and welding systems

> COMPATIBLE IMT CRANES

- 12000
- 10000
- 8600
- 7500
- 6000



REAR ACCESS PACKAGE

The rear access package features an extended handle and an extra step, in keeping with the Occupational Safety and Health Administration's three points of contact. The handle provides more surface for two hands to make contact, while the extra step reduces the height of the initial step as well as the distance between steps. This new standard access package is available curbside and roadside.



ENERGY-ABSORBING BOOM SUPPORT

The boom support is built standard with molded urethane in place of rubber. The shock absorbing, weatherproof urethane is formed over sheet metal, which provides dependable support. The revised support eliminates finicky seating issues and enhances the user's ability to visually fit the support.



MASTER LOCK SYSTEM

IMT is proud of its new, optional master lock system, which eradicates inadvertent operation of the lock. The new master lock is a spring-loaded system with a push-pull operation that ensures a secure lock every time.

NOTHING SAYS COMMITMENT LIKE THE DIAMOND.™



An Oshkosh Corporation Company

Iowa Mold Tooling Co., Inc. | 500 Highway 18 West | Garner, Iowa 50438 | 800-247-5958 | imt.com

IMT reserves the right to make changes in engineering, design, and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. IMT, the IMT logo, Dominator and NOTHING SAYS COMMITMENT LIKE THE DIAMOND are registered trademarks or trademarks of Iowa Mold Tooling Co., Inc., Garner, IA, USA. © 2017 Iowa Mold Tooling Co., Inc. All Rights Reserved.

